

Topcoat


F759 Matting Agent

Product Description

Allows reducing the gloss level of 2K solid colors and clears.

Pre-treatment

See process described in TDS of Dobte Solid Topcoats and clear coats

	Mixing Ratio	Stir well before use. Option 1: When F759 is contained in the mixing formula: Mix the components respecting the amounts specified in the mixing formula. Prepare the paint for application by adding hardener and thinner as indicated in the TDS of the solid topcoat/ clear coat being adjusted. Option 2: When matting an original glossy topcoat/clearcoat: Add to produce the desired degree of matting. <table><tr><td colspan="2">Semi Gloss:</td><td colspan="2">2K Clears</td></tr><tr><td>2K Solids</td><td>100(vol)</td><td>F759</td><td>100(vol)</td></tr><tr><td>F759</td><td>30(vol)</td><td>F759</td><td>30(vol)</td></tr><tr><td colspan="2">Satin Gloss:</td><td colspan="2">2K Clears</td></tr><tr><td>2K Solids</td><td>100(vol)</td><td>F759</td><td>100(vol)</td></tr><tr><td>F759</td><td>50(vol)</td><td>F759</td><td>50(vol)</td></tr><tr><td colspan="2">Silky Gloss:</td><td colspan="2">2K Clears</td></tr><tr><td>2K Solids</td><td>100(vol)</td><td>F759</td><td>100(vol)</td></tr><tr><td>F759</td><td>100(vol)</td><td>F759</td><td>100(vol)</td></tr></table> Stir well. Prepare the paint for application by adding hardener and thinner as indicated in the TDS of the solid topcoat/clear coat being adjusted.	Semi Gloss:		2K Clears		2K Solids	100(vol)	F759	100(vol)	F759	30(vol)	F759	30(vol)	Satin Gloss:		2K Clears		2K Solids	100(vol)	F759	100(vol)	F759	50(vol)	F759	50(vol)	Silky Gloss:		2K Clears		2K Solids	100(vol)	F759	100(vol)	F759	100(vol)	F759	100(vol)
	Semi Gloss:		2K Clears																																			
	2K Solids	100(vol)	F759	100(vol)																																		
F759	30(vol)	F759	30(vol)																																			
Satin Gloss:		2K Clears																																				
2K Solids	100(vol)	F759	100(vol)																																			
F759	50(vol)	F759	50(vol)																																			
Silky Gloss:		2K Clears																																				
2K Solids	100(vol)	F759	100(vol)																																			
F759	100(vol)	F759	100(vol)																																			
	Spray Guns	<table><tr><td>HVLP gravity-feed spraygun</td><td>1.2–1.3mm</td><td>1.8–2.0 bar</td><td>10–15 cm</td></tr><tr><td>Conventional gravity-feed spraygun</td><td>1.3–1.6mm</td><td>3.0–4.0 bar</td><td>15–20 cm</td></tr></table>	HVLP gravity-feed spraygun	1.2–1.3mm	1.8–2.0 bar	10–15 cm	Conventional gravity-feed spraygun	1.3–1.6mm	3.0–4.0 bar	15–20 cm																												
	HVLP gravity-feed spraygun	1.2–1.3mm	1.8–2.0 bar	10–15 cm																																		
Conventional gravity-feed spraygun	1.3–1.6mm	3.0–4.0 bar	15–20 cm																																			
	Application	Number of spraycoats: 1half wet + 1 wet coat Film thickness: 40-60 µm Dust-free until mat between spraycoats and before stoving.																																				